

# TOSHIBA B-SX8

## Specifications

Model	B-SX6	B-SX8
Technology	Thermal transfer / direct thermal	
Printhead	Edge type	
Resolution	12 dots/mm (305 dpi)	
Print Width	Maximum 170.6 mm	Maximum 213.3 mm
Print Length	Maximum 1705 mm	Maximum 1364 mm
Print Speed	Up to 203 mm/s	
Ribbon Save	Option	Standard
Interfaces	Bidirectional parallel port, USB 2.0, LAN (100BASE), serial port*, wireless LAN*	
Barcodes	UPC/EAN/JAN, Code 39, Code 93, Code 128, EAN 128, NW7, MSI, Industrial 2 of 5, ITF, Postnet, RM4SCC, KIX-code, RSS14, Customer Bar Code	
2D Codes	Data Matrix, PDF 417, Maxicode, QR code, Micro PDF 417, CP Code	
Fonts	Bitmap font (21 fonts), Outline font (4 types), Price font (3 types)	
Optional	Cutter module, strip module, ribbon save module (standard on B-SX8), wireless LAN module, serial interface board, expansion I/O board, RTC (real time clock), metal cover**, RFID kit**	
Dimensions	416 (W) x 289 (D) x 395 (H) mm	
Weight	25 kg (without media and ribbon)	

\* Option, \*\* Available 2007



TOSHIBA TEC Systems Integrator

**AUGUST INDUSTRIAL SUPPLIES**  
 14 Robinson Road, #13-00, Far East Finance Building  
 sales@august-industrial.com  
 Contact: (+65)6402 3278 Fax: (+65)6401 8631  
 www.august-industrial.com

## Options

The B-SX6 and B-SX8 printers can be extended with various modules:

- ☒ Cutter module  
A swing cutter to physically separate labels or continuous media automatically after printing.
- ☒ Peel Off module  
This module strips the label from the backing paper.
- ☒ Expansion I/O Interface board  
This option allows connection to external automated systems such as applicators or on-line verifiers.
- ☒ Real-time clock
- ☒ RFID kits (HF & UHF)
- ☒ Ribbon save (B-SX6 only).

All features and specifications described in this brochures are subject to change without notice.

All company and/or products names are trademarks and/or registered trade marks of their respective owners.